

D SUB MIXED MA CRIMP/CRIMP COAX 75 OHMS_



Image is for illustration purposes only. Please refer to product description.

Part number	09 69 282 7233
Specification	D SUB MIXED MA CRIMP/CRIMP COAX 75 OHMS_
HARTING eCatalogue	https://b2b.harting.com/09692827233

Identification

Category	Contacts
Series	D-Sub
Identification	Mixed
Type of contact	Coaxial contact
Description of the contact	Straight for cables RGD 179
Features	Tool setting: 5 for AWG 24 and AWG 26, 4 for AWG 28, 3 for AWG 30 Outer ferrule: crimp in tool cavity B

Version

Termination method	Crimp/crimp termination
Gender	Male
Manufacturing process	Turned contacts

Technical characteristics

Rated current	≤2 A
Rated voltage	250 V
Insulation resistance	>10 ⁹ Ω
Impedance	75 Ω
Stripping length	3 mm for inner contact die 4.3 mm Shielding 9.3 mm cable jacket
Limiting temperature	-55 ... +135 °C
Insertion force	≤7 N



Pushing Performance
Since 1945

Technical characteristics

Withdrawal force	≤7 N
Performance level	3
Mating cycles	≥50
Test voltage $U_{r.m.s.}$	0.75 kV @ 50 Hz
Frequency	0 ... 2 GHz

Material properties

Material (contacts)	Copper alloy PBFE / PBTP / PI
Surface (contacts)	Gold plated
Material (locking)	Copper alloy
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	339476a1-86ba-49e9-ab4b-cd336420d72a
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Commercial data

Packaging size	1
Net weight	2.51 g
Country of origin	Czechia
European customs tariff number	85366910
GTIN	5713140099449
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors