

## Adapter M12-RJ45 Right Angled



Image is for illustration purposes only. Please refer to product description.

Part number	21 03 381 4400
Specification	Adapter M12-RJ45 Right Angled
HARTING eCatalogue	<a href="https://b2b.harting.com/21033814400">https://b2b.harting.com/21033814400</a>

### Identification

Category	Accessories
Series	Circular connectors M12 RJ45
Connector 1	Female 4 poles RJ45
Type of accessory	Adapter
Description of the accessory	Panel feed through

### Version

Gender	Female
Coding	D-coding

### Technical characteristics

Rated current	4 A
Rated voltage	48 V AC 60 V DC
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 ... +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Thickness of the panel	2.1 ... 4.5 mm



## Material properties

Material (insert)	Liquid crystal polymer (LCP)
Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Specifications	IEC 61076-2-101
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size	1
Net weight	35.2 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140138292
ETIM	EC002943
eCl@ss	27440292 Connector component (accessories)