

## AIDA H-distributor



Image is for illustration purposes only. Please refer to product description.

Part number	61 12 204 0001 02
Specification	AIDA H-distributor
HARTING eCatalogue	<a href="https://b2b.harting.com/6112204000102">https://b2b.harting.com/6112204000102</a>

### Identification

Category	Connectors
Series	Han <sup>®</sup> PushPull (V14)
Identification	AIDA H-distributor
Element	Connector
Specification	Distributor AIDA compliant
Features	Intuitive locking mechanism

### Version

Termination method	Han <sup>®</sup> PushPull (V14)
Locking type	PushPull
Number of contacts	5
Pack contents	Distributor 2 fixing screws 4 Transport protection covers 2 distance sleeves

### Technical characteristics

Conductor cross-section	0.75 ... 2.5 mm <sup>2</sup>
Conductor cross-section	AWG 18 ... AWG 13
Rated current	15 A
Rated voltage	24 V
Rated impulse voltage	4 kV
Pollution degree	3



Pushing Performance

## Technical characteristics

Stripping length	10 mm Conductors 44 mm cable jacket
Tightening torque	3 Nm
Limiting temperature	0 ... +55 °C
Storage temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65

## Material properties

Material (insert)	Polyamide (PA)
Material (contacts)	Copper alloy
Surface (contacts)	Sn over Ni Termination side Au over Ni Mating side
Material (hood/housing)	Zinc die-cast

## Specifications and approvals

Approvals	DNV GL
-----------	--------

## Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440190 Industry connector (unspecified)