




TE Internal #: 2040002-1  
 B, 2.0, Micro Profile, Receptacle, 1 Port, Top, Right Angle, Tape &  
 Reel, Offset, Surface Mount, Cable-to-Board, 5 Position, USB  
 Connectors

[View on TE.com >](#)

Connectors > Audio & Video Connectors > USB Connectors



USB Adapter Type: **B**  
 USB Version: **2.0**  
 Connector Profile: **Micro**  
 Connector & Housing Type: **Receptacle**  
 Number of Ports: **1**

**Features**

**Product Type Features**

Integral Locking Latch	Without
USB Adapter Type	B
USB Version	2.0
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
USB Connector Type	Micro USB 2.0 Type-B

**Configuration Features**

Number of Ports	1
Number of Positions	5

**Body Features**

Shell Plating Finish	Bright
Shell Plating Material	Reflowed Tin over Nickel
Offset	0 mm



Connector Profile	Micro
-------------------	-------

### Contact Features

Contact Mating Area Plating Material Thickness	.76 $\mu\text{m}$ [29.52 $\mu\text{in}$ ]
Contact Mating Area Plating Material	Gold (Au)
Contact Current Rating (Max)	1.8 A

### Termination Features

Termination Post & Tail Length	.75 mm[.03 in]
Termination Method to PCB	Surface Mount

### Mechanical Attachment

Locking Feature	Without
PCB Mount Location	Top
PCB Connector Seating	Offset
PCB Mount Retention Type	Straight Leg
Panel Mount Feature Type	Flange
Connector Mounting Type	Board Mount

### Housing Features

Housing Color	Black
Housing Material	Thermoplastic
Body Orientation	Right Angle
Centerline (Pitch)	.65 mm[.025 in]

### Dimensions

PCB Thickness (Recommended)	.8 – 1. mm[.031 – .039 in]
-----------------------------	----------------------------

### Usage Conditions

Soldering Temperature (Max)	260 $^{\circ}\text{C}$ [500 $^{\circ}\text{F}$ ]
Mating Cycles (Max)	10000
Operating Temperature Range	-30 – 85 $^{\circ}\text{C}$ [-22 – 185 $^{\circ}\text{F}$ ]

### Operation/Application

Halogen Free	No
Assembly Process Feature	Without Pick and Place Cover
Circuit Application	Power & Signal

### Industry Standards

Industry Standard	USB 2.0
-------------------	---------



Moisture Sensitivity Level	1
Test Identification (TID)	62001336
UL Flammability Rating	UL 94V-0

### Packaging Features

Packaging Quantity	1000
Packaging Method	Tape & Reel

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Customers Also Bought



TE Part #1-211431-5  
SKT, SZ 22, PST, SD, ARINC 600




TE Part #1-84953-4  
1MM FPC HORZ. TOP CONT. ASSY 14P



TE Part #5-104074-8  
06 SYSTEM 50 HDR SRRA SHRD SN



TE Part #5499913-3  
A/L UNIV HDR 16P RA SHT LAT



TE Part #292253-8  
CT CONN MT HDR ASSY H 8P NAT



TE Part #5-104071-8  
06 SYSTEM 50 HDR SRST SHRD SN



TE Part #3-2176363-6  
RQ 0402 1K0 0.1% 10PPM 5K RL



TE Part #84953-8  
1MM FPC HORZ. TOP CONT. ASSY 8P



TE Part #6274127-1  
JACK, PCB, 75 OHM, R/A, BNC



TE Part #2-644486-3  
03P MTA100 SHRDED HDR ASSY SN

## Documents

### Product Drawings

#### MICRO USB, TYPE B

English

### CAD Files

#### 3D PDF

3D

#### Customer View Model

[ENG\\_CVM\\_CVM\\_2040002-1\\_E.2d\\_dxf.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_2040002-1\\_E.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_2040002-1\\_E.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages



## [5-1773464-3\\_Quick\\_Reference\\_Guide\\_Micro\\_USB\\_Connectors](#)

English

---

### **Product Specifications**

[Product Specification](#)

Japanese

---

### **Instruction Sheets**

[Instruction Sheet \(non U.S.\)](#)

Japanese